

5 User Pico 4 Ultra Enterprise Kit Specifications:

DEVICES Pico 4 Ultra Enterprise

Operating system
Pico OS

System architecture/processor
Qualcomm Snapdragon XR2 Gen 2

Memory (RAM)
12 GB

Storage(ROM)
256 GB Internal

Weight
580g with headstrap

Display
Resolution: 2160x 2160 (x2)
1200PPI (Pixels Per Inch)
90Hz Refresh Rate

Battery Life
Approx 3-4 hours

Connectivity
USB Type-C
WiFi Streaming

Bluetooth® technology
Yes

Wi-Fi
WiFi 7

Speakers/microphones
Integrated stereo speakers
Mic

Sensors
Hand tracking



Product Dimensions

Product Dimensions w640mm x d440mm x h380mm
Weight 21kg

INCHARGE CART

VR cases and Parotec specifications of electrics. Parotec Approvals:
CE Approved
ISO 9001 registered (2008)
Solutions based around our 16 & 36 x Port PCB Intelligence Board have been subject to testing at Cass Industries Limited an compliance testing and CE marking partner for UK & EU requirements.

Parotec PCB Boards:
PCB Inner board Power consumption:
5V @ 34A maximum supply (each port is current limited to 2.1A)
Robust design with up to 35 possible fixing holes on uniform 25mm centres
IEC/EN 60335 compliant and CE certified
Input voltage required up to 5.3V

Charge & Sync version of PCB also UL (USA) approved
*Charge Only boards currently used for VR kits. IF sending to US we would add Charge & Sync PCB's.

Parotec: Explorer Cases. Used to house all VR Kit.

Where no modification to the physical case is made these are fully waterproof and dust free.

Where we may have added external cooling fans the cases are reduced to weather proof and dust free.